



TECHNICAL DATASHEET

WWW.JACOBI.NET



JACOBI
THE CARBON COMPANY

AddSorb® VB1 impregnated coal based activated carbon

Features and Benefits

- Chemically impregnated
- Consistent quality
- Exceptional hardness and strength
- Rigorously dedusted
- Maximum loading capacity
- Minimal product degradation giving low pressure drop
- Clean handling at adsorber loading and commissioning

Typical Applications

- Chemical storage tank venting
- Purification of process gases
- Office air recirculation systems
- Laboratory fume hood filters

Available Pellet Diameters

- 2.0 mm diameter
- 3.0 mm diameter
- 4.0 mm diameter

AddSorb® VB1 is a high activity extruded activated carbon manufactured by steam activation from select grades of anthracite coal. AddSorb® VB1 is chemically impregnated for the control of inorganic alkali gases, such as ammonia, amines and caustic fumes in vapour phase applications. The careful chemical impregnation allows for a high removal efficiency while maintaining a high capacity for contaminant removal. For these reasons, AddSorb® VB1 can be used in a variety of applications, including the protection of critical equipment. AddSorb® VB1 is manufactured in dedicated production facilities, ensuring a high degree of product consistency and stability.



AddSorb® VB1 impregnated activated carbon is an efficient and economical activated carbon designed for the removal of inorganic alkali gases.

Specification*

CTC activity (base carbon)	min. 60%
Moisture content	max. 15%
Total ash content (base carbon)	max. 15%
Ball-pan hardness (base carbon)	min. 95%
Phosphoric acid content	min. 10%

Typical Properties*

Apparent density	630 kg/m ³
Pellet diameter	± 10% diameter

Standard Packaging

- 25 kg bag (55 lb)
- 500 kg bulk bag (1100 lb)



The polyethylene valve bag from Jacobi sets the standard in the industry for clean, durable and safe handling.

* Specifications and typical properties are produced using Jacobi Carbons' test methods. They are listed for informational purposes only and not to be used as purchase specifications. Sales specifications can be obtained from your Jacobi Carbons Technical Sales Representative and should be reviewed before placing an order.

ADDVB1-DSE-C0904



Jacobi
THE CARBON COMPANY



Polyethylene valve bags,
20 bags per pallet.



Polypropylene liner-free
FIBCs (super sacks),
2 bags per pallet.

CAUTION Activated carbon is a strong oxidizing agent and can remove oxygen from air under wet or humid conditions. Care should be taken when entering confined spaces where wet activated carbon is present. Ensure the use of correct breathing apparatus. Material Safety Data Sheets should be consulted for further details on procedures in the event of contact with activated carbon.

NOTICE Due to the progressive nature of the Jacobi Carbons Group and the continually improving design and performance of our products, we reserve the right to change product specifications without prior notification. The information contained in this datasheet is intended to assist a customer in the evaluation and selection of products supplied by Jacobi Carbons. The customer is responsible for determining whether products and the information contained in this document are appropriate for customer's use. Jacobi Carbons assumes no obligation or liability for the usage of the information in this datasheet, no guarantees or warranties, expressed or implied, are provided. Jacobi Carbons disclaims responsibility and the user must accept full responsibility for performance of systems based on this data.

WORLDWIDE DISTRIBUTORS A diverse network of agents, strategically located around the world. Please contact any Jacobi Carbons office to locate your nearest distributor. AquaSorb®, EcoSorb®, GoldSorb®, ColorSorb®, DioxSorb®, AddSorb® and Jacobi are registered trademarks of Jacobi Carbons.
© Jacobi Carbons, 2009.

ISO 9001
BUREAU VERITAS
Certification

